

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number  
**WO 2004/029941 A1**

(51) International Patent Classification<sup>7</sup>: G11B 7/00, 11/00

(74) Agents: BAHNG, Hae Cheol et al.; Kims International Patent & Law Office, 15th Floor, Yo Sam Building, 648-23, Yeoksam-dong, Kangnam-gu, Seoul 135-080 (KR).

(21) International Application Number:  
PCT/KR2003/002009

(22) International Filing Date:  
30 September 2003 (30.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
10-2002-0059341  
30 September 2002 (30.09.2002) KR  
10-2003-0011832  
25 February 2003 (25.02.2003) KR

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant: LG ELECTRONICS INC. [KR/KR]; 20, Yoido-dong, Youngdungpo-gu, Seoul 150-721 (KR).


(72) Inventors: PARK, Yong Cheol; 215-204, Jugong APT., Wonnun-dong, Gwachon-si, Gyeonggi-do 427-030 (KR). KIM, Sung Dae; 1110-1406, Jugong APT., Sanbon 1(il)-dong, Gunpo-si, Gyeonggi-do 435-746 (KR).

## Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: WRITE-ONCE OPTICAL DISC, AND METHOD AND APPARATUS FOR RECORDING MANAGEMENT INFORMATION ON WRITE-ONCE OPTICAL DISC



(57) Abstract: A write-once optical recording medium, and a method and apparatus for recording management information on the recording medium are provided. The method includes recording, in a temporary defect management area (TDMA), management information produced while the recording medium is in use, and transferring and recording the latest management information of the TDMA in a final defect management area (DMA) of the recording medium at a DMA fill-in stage of the recording medium.

WO 2004/029941 A1



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**WRITE-ONCE OPTICAL DISC, AND METHOD AND  
APPARATUS FOR RECORDING MANAGEMENT INFORMATION ON  
WRITE-ONCE OPTICAL DISC**

**5    Technical Field**

The present invention relates to a writable-once optical disc and a management information recording method and apparatus, and more particularly, to a method and apparatus for efficiently recording management information on a  
10    writable-once optical disc.

**Background Art**

Optical disc, which is a kind of optical recording media and can record a large  
15    amount of data, is widely being used. Today, a kind of innovative high-density digital versatile disc (HD-DVD) such as a blue ray disc (Blu-ray Disc), which can record and store video data of high quality and audio data of high fidelity for a long time, is under development.

The Blu-ray disc is a next generation optical recording solution that can store  
20    a larger amount of data than a conventional DVD. The Blu-ray disc employs a blue-violet laser with the wavelength of 405 nm which is shorter than the wavelength of 650 nm of a red laser used to access a conventional DVD. The Blu-ray disc has generally a thickness of 1.2 mm and a diameter of 12 cm. It includes a light transmission layer whose thickness is 0.1 mm so that the Blu-ray disc can store a  
25    larger amount of data than the current DVDs.

Various standards related to the Blu-ray discs are in development. Among the different types of Blu-ray discs, a Blu-ray Disc Rewritable (BD-RE) and a Blu-ray Disc Write-Once (BD-WO) are being developed.

FIG. 1 schematically illustrates a structure of a recording area of a general

BD-RE. Referring to FIG. 1, the BD-RE includes a recording layer divided into a lead-in area, a data area and a lead-out area. The data area includes a user data area for recording user data thereon, and an inner spare area ISA0 and an outer spare area OSA0 each allocated in the inner tracks and the outer tracks of the disc. These spare areas are used as replacement areas for replacing data in a defective area of the user data area according to linear replacement.

In the BD-RE, if a defective area is found in the user data area during recording, data in the defective area is transferred to and recorded on a spare area. Further, as defect management information for managing the defective area, position information and the like relating to the defective area and the corresponding spare area are recorded on defect management areas (DMA 1 ~ DMA 4) in the lead-in area and the lead-out area. Also, since data can be recorded on and erased from any area of the BD-RE repeatedly (since the BD-RE is rewritable), the entire BD-RE can be randomly used irrespective of a specific recording mode.

In contrast, in a writable-once Blu-ray disc (BD-WO), data can be recorded only one time on a specific area of the disc. As a result, the BD-WO has certain limitations pertaining to recording modes and in randomly using the entire area of the disc due to the defect management difficulty.

Further, in a BD-WO, management of the defective areas is one of the important matters that needs to be addressed, especially for data recording operations. But since the BD-WO is still in the early development stage, there are no schemes, no disc structures, no apparatuses, and no methods on how to manage the defective areas of the BD-WO and record management information on the BD-WO, which will be needed for the BD-WO to be commercially viable and operationally feasible. Accordingly, for the BD-WO, a unified specification is required that would satisfy the aforementioned advanced requirements. But any proposed specification relating to the current BD-RE cannot be used because it does not address the needs of the BD-WO.

**Disclosure of Invention**

Accordingly, the present invention is directed to a writable-once optical disc and a management information recording method and apparatus that substantially  
5 obviate one or more problems due to limitations and disadvantages of the background art.

An object of the present invention is to provide a method of recording disc management information such as timing, contents and location information in a plurality of management areas of a write-once optical disc.

10 Additional advantages, objects, and features of the invention will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the invention. The objectives and other advantages of the invention may be realized and attained by the structure particularly pointed out in the written  
15 description and claims hereof as well as the appended drawings.

To achieve these objects and other advantages and in accordance with the purpose of the invention, as embodied and broadly described herein, a method of recording management information on a write-once optical recording medium, the recording medium including a temporary defect management area (TDMA) and a  
20 final defect management area (DMA), includes: recording, in the TDMA, management information produced while the recording medium is in use; and transferring and recording the latest management information of the TDMA in the DMA at a DMA fill-in stage of the recording medium.

In accordance with an aspect of the invention, a method of recording  
25 management information on a write-once optical recording medium, the recording medium including a temporary defect management area (TDMA) and a final defect management area (DMA), the DMA including a defect list area for storing therein defect list information, includes: if no defect management is to be performed on the recording medium, setting a predetermined value in the defect list area of the DMA;

recording, in the TDMA, management information produced while the recording medium is in use; and transferring and recording the latest management information of the TDMA in the DMA when the recording medium is to be finalized.

In accordance with another aspect of the invention, an apparatus for recording  
5 management information on a write-once optical recording medium, the recording medium including a temporary defect management area (TDMA) and a final defect management area (DMA), includes a combination of elements configured for: recording, in the TDMA, management information produced while the recording medium is in use; and transferring and recording the latest management information  
10 of the TDMA in the DMA at a DMA fill-in stage of the recording medium.

In accordance with another aspect of the invention, an apparatus for recording management information on a write-once optical recording medium, the recording medium including a temporary defect management area (TDMA) and a final defect management area (DMA), the DMA including a defect list area for storing therein  
15 defect list information, includes a combination of elements configured for: setting a predetermined value in the defect list area of the DMA if no defect management is to be performed on the recording medium; recording, in the TDMA, management information produced while the recording medium is in use; and transferring and recording the latest management information of the TDMA in the DMA when the  
20 recording medium is to be finalized.

In accordance with another aspect of the invention, a write-once optical recording medium for recording management information thereon, includes: at least one recording layer including a temporary defect management area (TDMA) and a final defect management area (DMA), wherein management information produced  
25 while the recording medium is in use is recorded in the TDMA, and the latest management information of the TDMA is transferred and recorded in the DMA at a DMA fill-in stage of the recording medium.

In accordance with another aspect of the invention, a write-once optical recording medium for recording management information thereon, includes: at least

one recording layer including a temporary defect management area (TDMA) and a final defect management area (DMA), the DMA including a defect list area for storing therein defect list information, wherein if no defect management is to be performed on the recoding medium, a predetermined value is set in the defect list area of the DMA; management information produced while the recording medium is in use is recorded in the TDMA; and the latest management information of the TDMA is transferred and recorded in the DMA when the recording medium is to be finalized.

It is to be understood that both the foregoing general description and the following detailed description of the present invention are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

#### **Brief Description of the Drawings**

15

Further objects and advantages of the invention can be more fully understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

FIG. 1 schematically illustrates a structure of a general single-layer BD-RE:

20 FIG. 2 is a block diagram of an optical recording/reproducing device according to the present invention;

FIG. 3 illustrates a structure of a writable-once optical disc such as a single layer BD-WO according to an embodiment of the present invention;

25 FIG. 4 illustrates an example of a DDS structure on a rewritable disc, a TDDS structure on a BD-WO and a disc management information recording method for the BD-WO according to an embodiment of the present invention;

FIG. 5 illustrates a structure of a writable-once optical disc such as a single layer BD-WO according to another embodiment of the present invention;

FIG. 6A shows an exemplary structure of a DMA of a single-layer BD-WO

according to an embodiment of the present invention;

FIG. 6B illustrates the structure of the DMA of FIG. 6A, a TDMA structure and a method of transferring data from the TDMA to the DMA according to an embodiment of the present invention;

5        FIG. 6C shows an exemplary structure of a DMA of a dual-layer BD-WO according to an embodiment of the present invention;

FIG. 7 shows a chart for explaining the timing, contents and location information associated with the DMA fill-in process of a BD-WO according to a first embodiment of the present invention;

10        FIG. 8 shows a chart for explaining the timing, contents and location information associated with the DMA fill-in process of a BD-WO according to a second embodiment of the present invention;

FIG. 9A shows a chart for explaining the timing, contents and location information associated with the DMA fill-in process of a BD-WO according to a  
15        third embodiment of the present invention;

FIG. 9B shows an example of the DMA to which the DMA fill-in process of FIG. 9A is applied; and

FIG. 10 shows examples of values of a TDDS/DDS status flag recorded as part of the DDS information in the DDS section of the DMA according to the present  
20        invention.

### **Best mode for Carrying Out the Invention**

Reference will now be made in detail to the preferred embodiments of the  
25        present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numerals will be used throughout the drawings to refer to the same or like parts.

FIG. 2 is an example of a block diagram of an optical disc recording/reproducing device 20 according to an embodiment of the present



invention. The optical disc recording/reproducing device 20 includes an optical pickup 22 for writing/reading data to/from an optical recording medium 21, a servo unit 23 for controlling the pickup 22 to maintain a distance between an objective lens of the pickup 22 and the recording medium 21 and for tracking relevant tracks on the recording medium 21, a data processor 24 for processing and supplying input data to the pickup 22 for writing, and for processing data read from the recording medium 21, an interface 25 for exchanging data and/or commands with any external host 30, a memory or storage 27 for storing information and data therein including defect management data as needed (e.g., temporary defect management information, etc.) associated with the recording medium 21, and a microprocessor or controller 26 for controlling the operations and elements of the recording/reproducing device 20. Data to be written/read to/from the recording medium 21 may also be stored in the memory 27 if needed. All the components of the recording/reproducing device 20 are operatively coupled. The recording medium 21 is a recording medium of write-once type such as a BD-WO.

All the methods and disc structures discussed herein according to the present invention can be implemented using the recording/reproducing device 20 of FIG. 2 or any other suitable device/system. For example, the microcomputer 26 of the device 20 may be used to control allocation of the disc structure and to control the recording of management information on the recording medium and the transferring of the management information from a temporary area (e.g., TDMA) to a permanent or final area (e.g., DMA) on the recording medium 21. The TDMA and DMA will be discussed later in more detail.

A management information recording method for a writable-once optical disc such as a BD-WO according to the preferred embodiments of the present invention will be now described in detail with reference to the accompanying drawings. For a discussion convenience, a writable-once Blu-ray disc (BD-WO) will be exemplified. Herein, two types of a BD-WO - a single layer BD-WO and a dual layer BD-WO - are discussed. The single layer BD-WO has a single recording layer, whereas the

dual layer BD-WO has two recording layers.

FIG. 3 illustrates a structure of a writable-once optical recording medium such as a single-layer BD-WO according to an embodiment of the present invention. Referring to FIG. 3, the BD-WO includes a lead-in area, a data area, and a lead-out area allocated on the single recording layer. Each of the lead-in area and the lead-out area includes a plurality of defect management areas (DMA 1 and DMA 2; DMA 3 and DMA 4) for storing therein DMA information for defect management. Each of the DMAs 1-4 has a fixed size, e.g., 32 clusters. Generally, in view of the importance of defect management, the same information is written in each of the DMAs 1-4 so that if one of the DMAs is defective, then a different DMA can be accessed to obtain the defect management information.

It should be noted that in a general BD-RE, since data can be repeatedly recorded on and erased from a DMA (although the size of the DMA is limited), a DMA of large size is not required. However, in a BD-WO according to the present invention, since data cannot be repeatedly recorded on and erased from the DMA, a DMA of large size is required for defect management.

Still referring to FIG. 3, the lead-in area further includes a temporary defect management area (TDMA 1) for temporarily storing defect management information therein. The data area includes an inner spare area ISA0, a user data area, and an outer spare area OSA0. Parts of or the entire ISA0 and OSA0 are used as replacement areas for defective areas in the user data area according to linear replacement. For instance, during a recording of data into the user data area, if a defective area in the user data area is detected, then the data written or to be written to this defective area is transferred to a spare area (e.g., ISA0 or OSA0) according to a linear replacement scheme. The outer spare area OSA0 includes a temporary defect management area (TDMA 2). The defect management information temporarily stored in the TDMA 1 and/or TDMA 2 is also referred to herein as TDMA information.

In one embodiment, the TDMA 1 allocated to the lead-in area has a fixed size,

whereas the TDMA 2 allocated to the outer spare area OSA0 has a variable size depending upon the size of the spare area(s). For example, if the OSA0 has a size of  $N \times 256$  clusters where  $N > 0$  ( $N = \text{integer}$ ), then the TDMA 2 has a size of  $P$  clusters where  $P = (N \times 256)/4$ .

5           In one example, the same information may be written in each of the TDMA 1 and 2. In another example, the TDMA 1 and 2 may be sequentially used to sequentially record the TDMA information. Regardless, during replacement writing operations for writing data of a defective area onto a spare area, TDMA information is generated (e.g., under control of the microcomputer 26) and written onto the  
10   TDMA 1 and/or 2. The TDMA 1 and/or 2 are also updated periodically or as needed. When the BD-WO is ready to be finalized or the DMA is to be filled in for other reasons, then the TDMA information (latest version) temporarily written in the TDMA(s) is transferred and written onto one or each of the DMA 1-4. This transfer process will be discussed later in more detail.

15           The TDMA information written in each of the TDMA 1 and 2 includes temporary defect list (TDFL) information and temporary disc definition structure (TDDS) information. In one embodiment, the TDFL information includes one or a plurality of TDFLs (TDFL #1 ~ TDFL #n). Each TDFL includes one or a plurality of defect entries identifying defects and corresponding replacement areas on the disc.  
20   Each defect entry includes location information pertaining to a defective area of the user data area and the corresponding replacement area. For example, during a data recording operation on the BD-WO, if a defective area is found in the user data area, then data written or to be written in that defective area is written in a part (replacement area) of a spare area (e.g., ISA0 or OSA0) according to a linear  
25   replacement scheme. Then the information pertaining to the defective area and the replacement area and their relationship is entered as a defect entry in the TDFL. For instance, this information may include a first physical sector number of the defective area on the disc, a first physical sector number of the replacement area (spare area) corresponding to that defective area, and any other data pertaining to the defect for

defect management.

In one embodiment, the TDDS information written in each of the TDMA 1 and 2 includes one or a plurality of TDDSs (TDDS #1 ~ TDDS #n). Each TDDS has a fixed size (e.g., one cluster) and includes location information pertaining to the TDFL(s) so that the location of any TDFL can be quickly identified by accessing the TDDS(s). This location information is also referred to herein as the TDDS part and can be written in a portion of Sector 0 of the one cluster. Here, a cluster has 32 sectors each sector having 2048 bytes. As an example only, the TDDS part may include one or more physical sector numbers each indicating a location of a TDFL written on the BD-WO, and any other information pertaining to the TDFL information.

Furthermore, each TDDS includes recording mode information (RM) and disc usage management information. The recording mode information identifies a recording mode of the BD-WO and can be written in a portion of Sector 0 of the one cluster. The disc usage management information identifies the status of a recording area of the BD-WO, and can be represented in one of the two forms: track information (Track-Info) and space bitmap information (SBM). This structure of the TDDS will be discussed in more detail later by referring to FIG. 4.

As the data recording operation for writing data into the data area progresses, the TDMA 1 and 2 may be updated periodically to reflect any recently discovered defective areas and corresponding replacement areas. After each updating of the TDMA, a TDFL and a corresponding TDDS, which may include all previous TDMA information and the recently generated TDMA information, may be written in the TDMA. In this aspect, the latest TDDS and TDFL written in the TDMA of the BD-WO would include the latest TDMA information. Then when the BD-WO is to be finalized or the DMA(s) is ready to be filled in, the latest TDDS and TDFL written on the BD-WO are transferred and written in one or each of the DMAs 1-4 as the final and most-updated defect management information.

FIG. 4 illustrates a DDS structure of a rewritable disc, an example of a TDDS

structure on a BD-WO and a disc management information recording method for the BD-WO according to an embodiment of the present invention. As shown in FIG. 4, in the DDS of a general rewritable optical disc, only 60 byte information corresponding to an extremely small portion of 1 cluster is used to store therein the DDS information. The entire remaining part of the DDS is all set to 'zero padding'.

In contrast, in the BD-WO, the entire TDDS area is used to store therein the TDDS information. As shown in FIGS. 3 and 4, the TDDS part and the recording mode information are written in Sector 0 of the cluster assigned as the TDDS, whereas Sectors 1-31 store therein the disc usage management information (Track-Info or SBM). In another example, the disc usage management information can be recorded on the first 31 sectors (Sectors 0 ~ 30) in the TDDS, and any remaining disc usage management information can be recorded on the last 32<sup>nd</sup> sector (Sector 31) in the TDDS along with the TDDS part and recording mode information.

The recording mode information identifies one of a plurality of recording modes employed in the BD-WO according to the present invention. In this example, a value of "0000 0000" may be used to indicate a sequential recoding mode, and a value of "0000 0001" may be used to indicate a random recording mode. Obviously, other examples are possible. Information about the BD-WO according to the present invention can be variously determined depending upon the needs through a process of specification regulation.

The disc usage management information is varied in dependence upon the disc usage. In the BD-WO, the disc usage management information is required for accurately searching and detecting the start point of an available recording area, and is used to distinguish a recording area from a non-recording area on the disc. In this aspect, the disc usage management information indicates where the available recording area and the recorded area are located within the data area (e.g., user data area).

As mentioned above, the disc usage management information can be represented as either the track information (Track-Info) or the space bitmap

information (SBM). The Track-Info is generally used when the BD-WO is recorded in a sequential recording mode. The SBM is generally used when the BD-WO is recorded in a random recording mode. These recording modes can be determined depending on the recording mode identified in the recording mode information  
5 stored in the TDDS.

In conventional writable-once optical discs, the recording status/mode information is expressed as 'track information' in case of compact disc series, and as 'Rzone', 'Fragment' or 'recording range' in case of DVD series. But in the present invention, the aforementioned various expressions relating to the recording  
10 status/mode information are commonly designated as 'Track-Info', and accordingly the Track-Info will be appreciated as having such meaning irrespective of expressions.

In one example, since the tracks on the BD-WO are sequentially used to record during the sequential recording mode, the Track-Info identifies the start point  
15 (location) of the recording area (e.g., user data area) of the BD-WO, and the end point (location) of the last recorded portion of the recording area. This information then indicates the start of the next available portion of the recording area on the BD-WO.

The bitmap information identifies a start point of an available recordable  
20 portion of the recording area on the BD-WO using bit values such as '0' and '1'. For instance, if a particular cluster area of the recording area on the BD-WO has been recorded, then it is indicated by allocating a value of '1' to every minimal recording unit (1 cluster). If a cluster area of the recording area has no recorded data thereon, then that cluster is assigned to a value of '0'. In this manner, if the SBM  
25 indicates that a particular cluster has a value of '1' assigned thereto, then it indicates that that cluster has been already used (i.e., it has recorded data thereon). If the SBM indicates that a particular cluster has a value of '0', then it indicates that that cluster has not been used yet (i.e., it has no recorded data thereon). Obviously, the reversal or some other values may be used to indicate the recording/non-recording state of

each area unit such as the clusters of the user data area. Thus, the SBM makes it possible to express a recording usage status of the disc even in the random recording mode.

FIG. 5 illustrates a structure of a writable-once optical disc such as a single layer BD-WO according to another embodiment of the present invention. The BD-WO structure of FIG. 5 is identical to the BD-WO structure of FIG. 3, except that the TDDS part and the recording mode information (RM) of TDDS information are updated and written after each update state as shown in FIG. 5. In this aspect, the disc usage management information (Track-Info or SBM) is stored in Sectors 0-30 of one cluster of the TDMA, and the TDDS part and RM are stored in Sector 31 of the one cluster. In another example, the TDDS part and RM may be stored in Sector 0 of one cluster of the TDMA, and the Track-Info or SBM may be stored in Sectors 1-31 of the one cluster.

Now, the method of transferring the TDMA information from the TDMA to the DMA according to the embodiments of the present invention will be explained by referring to FIGS. 6A-10. This transfer process is also called a DMA fill-in process.

FIG. 6A shows an exemplary structure of a DMA of a single-layer BD-WO, and FIG. 6B illustrates the structure of the DMA of FIG. 6A, a TDMA structure and a method of transferring data from the TDMA to the DMA according to an embodiment of the present invention. The DMA shown in FIGS. 6A and 6B equals one or each of the DMAs 1-4 shown in FIG. 3.

Referring to FIGS. 6A and 6B, the DMA is composed of 32 clusters. The Clusters 1-4 of the DMA are designated as a DDS section, whereas the Clusters 5-32 of the DMA are designated as a DFL section. All the clusters of the DMA in the BD-WO are designated for storing management data.

During the DMA fill-in process, the latest TDDS information from the TDMA is transferred to and recorded in each of Cluster 1 to Cluster 4 of the DMA as DDS information. In this example, the latest TDDS part (T0) and the latest disc

usage management information (Track-Info or SBM) (D0) of the TDDS information are transferred onto the DMA. As a result, the same DDS information is four times recorded in the DMA. The latest TDFL information from the TDMA is also transferred to and recorded in Clusters 5-32 of the DMA as DFL information. Here, 5 the same DFL information can be recorded in the DMA up to seven times by designating four clusters of the DMA for recording the DFL information therein. In one example, the TDDS part written in the DDS section of the DMA may identify the location of the DFLs in the DMA on the BD-WO, and not necessarily the location of the TDFLs in the TDMA on the BD-WO. Storing the same information 10 repeatedly in the DDS section or the DFL section ensures that the DMA information is not lost (e.g., due to a defect in a portion of the DMA) and is accurately and completely accessed each time it is needed.

FIG. 6C shows an exemplary structure of a DMA of a dual-layer BD-WO according to an embodiment of the present invention. Referring to FIG. 6C, one 15 DMA of the dual-layer BD-WO is composed of a DMA part (Clusters 1-32) from a first recording layer L0 of the BD-WO, and a DMA part (Clusters 33-64) from a second recording layer (L1) of the BD-WO, which are accessed according to the tracking direction indicated with the arrow. The same DDS information (e.g., for both recording layers) is repeatedly recorded on the Clusters 1 ~ 8 of the DMA, and 20 the same DFL information is repeatedly recorded on the Clusters 9 ~ 64 of the DMA, up to the maximum of, e.g., seven times. In addition, the BD-WO includes a lead-in area, a data area and an outer zone area on the first recording layer, and a lead-out area, a data area and an outer zone area on the second recording layer. Each of the data areas may include at least one spare area and a user data area. The lead-in area 25 of the first recording layer may include a TDMA and first and second DMAs. The lead-out area of the second recording layer may include another TDMA and first and second DMAs. Here, as an example, one DMA shown in FIG. 6C may be composed of the first DMAs from the first and second recording layers, or of the second DMAs from the first and second recording layers. Additional DMAs may also be provided



in the outer zone areas. The spare area(s) may include additional TDMA(s).

Similar to the single layer BD-WO, the TDMA(s) in the lead-in/lead-out area of the dual layer BD-WO may have a fixed size, whereas the TDMA(s) in the spare areas may have a variable size depending upon the size of the spare area(s). The use  
5 and structure of the DMAs and TDMA(s) on the single layer BD-WO as discussed herein applies equally to the DMAs and TDMA(s) on the dual layer BD-WO.

In one embodiment, the latest disc usage management information is recorded each on the front part of a first DMA in the lead-in area and/or on the front/rear part of a DMA in the lead-out area (depending on whether the disc has a single or  
10 multiple recording layers). This allows the disc usage management information to be accessed quickly at the initial loading time of the disc. Further, the data reliability and data preservation can be assured by repetitive recording of same information in different parts of the disc.

FIG. 7 shows a chart for explaining the timing, contents and location  
15 information associated with the DMA fill-in process of a BD-WO according to a first embodiment of the present invention. This DMA fill-in process is applicable to the BD-WO structures shown in FIGS. 3 and 5-6C, or other suitable BD-WO structures.

Referring to FIG. 7, the time for transferring the TDMA information into the DMA of the BD-WO is when the BD-WO is to be finalized. Defect management is  
20 performed on the BD-WO. As a result, the TDMA information produced while the BD-WO is in use is recorded in the TDMA, and when the BD-WO is to be finalized, the latest TDMA information from the TDMA is transferred to and recorded in the DMA.

The time for finalization is generally divided into three cases. The first case  
25 (50a) is when no more recording is performed on the BD-WO (e.g., data recording in the user data area is completed, or no user data area remains on the disc). The second case (50b) is when the TDMA is full of data and no further TDMA information can be recorded therein. As one example only, this case may occur if the entire TDMA(s) for recording the TDMA information have been used. The third case

(50c) is when the user requests a finalization of the BD-WO. As one example only, the user or host may request the finalization of the BD-WO even though some user data area or the TDMA is not full, or even though the user data recording in the user data area is not completed.

5           In all three cases of timing, the contents transferred from the TDMA to the DMA are the latest TDDS and TDFL information written in the TDMA of the BD-WO. The latest TDDS information and the latest TDFL information written in the TDMA are transferred to a DDS section and a DFL section of the DMA, respectively, during the DMA fill-in process.

10           FIG. 8 shows a chart for explaining the timing, contents and location information associated with the DMA fill-in process of a BD-WO according to a second embodiment of the present invention. This DMA fill-in process is applicable to the BD-WO structures shown in FIGS. 3 and 5-6C or other suitable BD-WO structures.

15           The second embodiment addresses a scenario when the defect management (DM) on the BD-WO is not to be performed. Whether or not the DM is to be performed on the BD-WO can be determined during the initialization of the BD-WO or some other time based on known factors such as a user or host command not to perform defect management, etc. Referring to FIG. 8, if it is determined that the DM  
20 is not to be performed (50d) on the BD-WO (e.g., when the disc is initialized), then a specified value, sign or other indication is set in a DFL section of the DMA. This indication indicates that no DM is performed on the BD-WO (e.g., no defect lists are recorded on the BD-WO or no linear replacement schemes are performed to transfer the data of a defective user area to a replacement/spare area). When no DM is to be  
25 performed, A/V (audio/video) data can be recorded in real time. Here, since no DM is performed during the disc recording (e.g., into the user data area), no TDFLs are generated and the predetermined value or some other fixed indication can be set in the DFL section of the DMA. In one example, the predetermined value for indicating no DM is set in the DFL section of the DMA in advance before the

finalization of the BD-WO (e.g., at the disc initialization). At this time, the entire DFL section of the DMA may be padded with the zero value. In another variation, a predetermined value (e.g., zero) or some other indication may be set in the TDFL area of the TDMA, and then this value (TDFL information) may be transferred to the DFL section of the DMA while the TDDS information is transferred to the DDS section of the DMA during the DMA-fill in process (i.e., at the finalization of the BD-WO).

The process of transferring the TDDS information from the TDDS of the TDMA to the DDS section of the DMA in the second embodiment is identical to that of the first embodiment of FIG. 7. More specifically, after it is determined that no DM is to be performed on the BD-WO and then when the BD-WO is ready to be finalized, then the TDDS information is transferred to the DDS section of the DMA. As shown in FIG. 8, during the finalization of the BD-WO, in the first case (50a) when no more recording is performed on the BD-WO, in the second case (50b) when the TDMA is full, and in the third case when the user requests finalization of the BD-WO, the latest TDDS information from the TDMA is transferred and recorded in the DDS section of the DMA as part of DMA fill-in process.

For example, if the DMA fill-in process of FIG. 8 is applied to the DMA structure of FIG. 6A, the Clusters 1-4 of the DMA would store therein the predetermined value (e.g., zero), and the latest TDDS information from the TDMA is transferred and recorded in the DDS section of the DMA. As discussed above, the same latest TDDS information can be recorded up to seven times in the Cluster 5-32 of the DMA. That is, in the maximum 7 repetition recording, the same latest TDDS information is written in the Clusters 5-8, the Cluster 9-12, the Cluster 13-16, ... and the Clusters 29-32 of the DMA.

FIG. 9A shows a chart for explaining the timing, contents and location information associated with the DMA fill-in process of a BD-WO according to a third embodiment of the present invention. This DMA fill-in process is applicable to the BD-WO structures shown in FIGS. 3 and 5-6C or other suitable BD-WO

structures.

The third embodiment addresses a scenario when no more data can be recorded in the user data area of the BD-WO, but the spare area(s) and the TDMA(s) are not full and can still be used to perform defect management. If any recordable area remains in the spare area (e.g., ISA0 and OSA0) and the TDMA (e.g., TDMA 1 and 2) even though no more recordable area exists in the user data area of the BD-WO (e.g., because the user data area is full, etc.), then at that time, the latest TDDS and TDFL information from the TDMA is transferred and recorded into an area of the DMA. Subsequently, when the BD-WO is ready to be finalized, the latest TDDS and TDFL information at that time from the TDMA is transferred and recorded into another area of the DMA, such as the remaining area of the DMA.

Referring to FIG. 9A, in this embodiment, the DM is performed even during the reproduction of the BD-WO. Particularly, if the spare area and the TDMA are not full and are available for use in the DM even though the recordable user data area is not available (50e), the latest TDMA information of the TDMA at this time is transferred and recorded in only a partial area of the DMA before the finalization of the BD-WO. Subsequently, when the BD-WO is to be finalized (50b or 50c), the latest TDMA information of the TDMA at that time is then transferred and recorded in the remaining or another area designated of the DMA.

Here, the time for finalization is divided into two cases 50b and 50c, which are identical to the two cases 50b and 50c in FIG. 7. Briefly, the first case (50b) is when the TDMA is full of data and no further TDMA information can be recorded therein. The second case (50c) is when the user requests a finalization of the BD-WO.

FIG. 9B shows an example of the DMA to which the DMA fill-in process of FIG. 9A is applied. As shown in FIG. 9B, when the situation 50e occurs, the latest TDDS information is written as DDS information into two clusters (e.g., Clusters 1 and 2) of the DMA, and the latest TDFL information is written as DFL information into four clusters (e.g., Clusters 5-8) of the DMA. Here the latest TDFL information

is written once in Clusters 5-8 without any repetition. Then when the disc is to be finalized (50b or 50c), the latest TDDS information of that time is written as DDS information into two clusters (e.g., Clusters 3 and 4) of the DMA and the latest TDFL information of that time is written as DFL information into the remaining  
5 clusters of the DMA. For instance, the same TDFL information can be written up to six times in the Clusters 9-32 of the DMA. Other variations are possible.

FIG. 10 shows examples of values of a TDDS/DDS status flag recorded as part of the DDS information in the DDS section of the DMA according to the present invention. Such status flag can be used in all the disc structures and methods  
10 discussed herein according to the different embodiments of the present invention. This status flag informs the user, host or other entity under which status/case the TDDS or DDS information has been recorded on the BD-WO. The TDDS or DDS status flag may be of one-byte size or some other size.

For instance, in each of the above-discussed first to third embodiments of the  
15 present invention, the DDS information written in the DDS section of the DMA may include a DDS status flag. Similarly, the TDDS information written in the TDMA may include a TDDS status flag. One status flag having different values may be used to indicate different recording statuses of the TDDS and DDS information. In the alternative, separate TDDS status flag and DDS status flag can be used.

20 Referring to FIG. 10, if the same status flag is used for both the TDDS and DDS information, then the status flag of '0000 0000' may mean that the BD-WO is finalized in response to the user's request (50c) and that the management information (e.g., DDS information) is recorded in the DMA. The status flag of '0000 1111' may mean that the BD-WO is finalized because no more recording is  
25 allowed in the user data area (50a) and that the management information (e.g., DDS information) is recorded in the DMA. The status flag of '1111 0000' may mean that the BD-WO is finalized because the TDMA is full (50b) and that the management information (e.g., DDS information) is recorded in the DMA. The status flag of '1111 1111' may mean that the management information (e.g., TDDS information)

is recorded in the TDMA while the disc is in use. Obviously other variations or status flag values are possible.

### **Industrial applicability**

5

Using the status flag discussed above, the status of the BD-WO can be determined or confirmed. For instance, when the disc is loaded for reproduction, the TDDS/DDS status flag value can be examined to determine under what circumstances and in what manner the DMA fill-in process occurred on the disc.

10 Thus, the efficient use of the disc can be assured.

It will be apparent to those skilled in the art than various modifications and variations can be made in the present invention. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

**What is claimed is:**

1. A method of recording management information on a write-once optical recording medium, the recording medium including a temporary defect management area (TDMA) and a final defect management area (DMA), the method comprising:

recording, in the TDMA, management information produced while the recording medium is in use; and

transferring and recording the latest management information of the TDMA in the DMA at a DMA fill-in stage of the recording medium.

2. The method of claim 1, wherein the DMA fill-in stage of the recording medium is when the recording medium is to be finalized.

3. The method of claim 2, wherein the recording medium is to be finalized when no more recording in a user data area of the recording medium is allowed.

4. The method of claim 3, wherein in the transferring step, the latest management information includes latest temporary defect list information and latest temporary disc definition structure information associated with the recording medium.

5. The method of claim 2, wherein the recording medium is to be finalized when the TDMA is full and no more management information can be recorded in the TDMA.

6. The method of claim 5, wherein in the transferring step, the latest management information includes latest temporary defect list information and latest temporary disc definition structure information associated with the recording

medium.

7. The method of claim 2, wherein the recording medium is to be finalized in response to a user's request.

5

8. The method of claim 7, wherein in the transferring step, the latest management information includes latest temporary defect list information and latest temporary disc definition structure information associated with the recording medium.

10

9. The method of claim 1, wherein the recording medium further includes a spare area and a user data area, and

wherein in the transferring step, the DMA fill-in stage is when a recordable area remains in the spare area and the TDMA even though no recordable area remains in the user data area of the recording medium, and latest management information of the TDMA at that time is transferred into a first area of the DMA.

15

10. The method of claim 9, further comprising:

transferring and recording latest management information of the TDMA into a second area of the DMA at a second DMA fill-in stage of the recording medium.

20

11. The method of claim 10, wherein the second DMA fill-in stage of the recording medium is when the recording medium is to be finalized.

25

12. The method of claim 11, wherein if the management information is recorded in the first area of the DMA, then a defect management is performed during reproduction of the recording medium; and if the management information is recorded in the second area of the DMA, then a defect management is not performed during reproduction of the recording medium.



13. The method of claim 11, wherein the recording medium is to be finalized when the TDMA is full and no more management information can be recorded in the TDMA.

5

14. The method of claim 13, wherein in at least one of the transferring steps, the latest management information includes latest temporary defect list information and latest temporary disc definition structure information associated with the recording medium.

10

15. The method of claim 11, wherein the recording medium is to be finalized in response to a user's request.

16. The method of claim 15, wherein in at least one of the transferring steps, the latest management information includes latest temporary defect list information and latest temporary disc definition structure information associated with the recording medium.

15

17. The method of claim 1, wherein the recording medium is a writable-once Blu-ray disc (BD-WO).

20

18. The method of claim 1, wherein in the transferring step, the latest management information includes a status flag indicating a type of the DMA fill-in stage.

25

19. A method of recording management information on a write-once optical recording medium, the recording medium including a temporary defect management area (TDMA) and a final defect management area (DMA), the DMA including a defect list area for storing therein defect list information, the method comprising:

if no defect management is to be performed on the recoding medium, setting a predetermined value in the defect list area of the DMA;

recording, in the TDMA, management information produced while the recording medium is in use; and

5       transferring and recording the latest management information of the TDMA in the DMA when the recording medium is to be finalized.

20. The method of claim 19, wherein the DMA further includes a disc definition structure area for storing therein disc definition structure information, and  
10       wherein in the transferring step, the latest management information of the TDMA is transferred to the disc definition structure area of the DMA and is latest disc definition structure information associated with the recording medium.

21. The method of claim 19, wherein the recording medium is to be finalized  
15       when no more recording in a user data area of the recording medium is allowed.

22. The method of claim 19, wherein the recording medium is to be finalized when the TDMA is full and no more management information can be recorded in the TDMA.

20

23. The method of claim 19, wherein the recording medium is to be finalized in response to a user's request.

24. The method of claim 19, wherein the recording medium is a writable-once  
25       Blu-ray disc (BD-WO).

25. The method of claim 19, wherein in the transferring step, the latest management information includes a status flag indicating a type of the finalization of the recording medium.

26. An apparatus for recording management information on a write-once optical recording medium, the recording medium including a temporary defect management area (TDMA) and a final defect management area (DMA), the apparatus comprising:

5        means for recording, in the TDMA, management information produced while the recording medium is in use; and

         means for transferring and recording the latest management information of the TDMA in the DMA at a DMA fill-in stage of the recording medium.

10        27. An apparatus for recording management information on a write-once optical recording medium, the recording medium including a temporary defect management area (TDMA) and a final defect management area (DMA), the DMA including a defect list area for storing therein defect list information, the apparatus comprising:

15        means for setting a predetermined value in the defect list area of the DMA if no defect management is to be performed on the recording medium;

         means for recording, in the TDMA, management information produced while the recording medium is in use; and

         means for transferring and recording the latest management information of  
20        the TDMA in the DMA when the recording medium is to be finalized.

28. A write-once optical recording medium for recording management information thereon, the recording medium comprising:

         at least one recording layer including a temporary defect management area  
25        (TDMA) and a final defect management area (DMA),

         wherein management information produced while the recording medium is in use is recorded in the TDMA, and

         the latest management information of the TDMA is transferred and recorded in the DMA at a DMA fill-in stage of the recording medium.

29. The recording medium of claim 28, wherein the DMA fill-in stage of the recording medium is when the recording medium is to be finalized.

5           30. The recording medium of claim 29, wherein the recording medium is to be finalized when no more recording in a user data area of the recording medium is allowed.

31. The recording medium of claim 30, wherein the latest management  
10 information transferred and recorded in the DMA includes latest temporary defect list information and latest temporary disc definition structure information associated with the recording medium.

32. The recording medium of claim 29, wherein the recording medium is to  
15 be finalized when the TDMA is full and no more management information can be recorded in the TDMA.

33. The recording medium of claim 32, wherein the latest management  
information transferred and recorded in the DMA includes latest temporary defect  
20 list information and latest temporary disc definition structure information associated with the recording medium.

34. The recording medium of claim 29, wherein the recording medium is to  
be finalized in response to a user's request.

25

35. The recording medium of claim 34, wherein the latest management  
information transferred and recorded in the DMA includes latest temporary defect  
list information and latest temporary disc definition structure information associated  
with the recording medium.

36. The recording medium of claim 28, wherein the at least one recoding layer further includes a spare area and a user data area, and

5 wherein the DMA fill-in stage is when a recordable area remains in the spare area and the TDMA even though no recordable area remains in the user data area of the recording medium, and latest management information of the TDMA at that time is transferred into a first area of the DMA.

37. The recording medium of claim 36, wherein latest management  
10 information of the TDMA is transferred and recorded into a second area of the DMA at a second DMA fill-in stage of the recording medium.

38. The recording medium of claim 37, wherein the second DMA fill-in stage of the recording medium is when the recording medium is to be finalized.  
15

39. The recording medium of claim 38, wherein if the management information is recorded in the first area of the DMA, then a defect management is performed during reproduction of the recording medium; and if the management information is recorded in the second area of the DMA, then a defect management is  
20 not performed during reproduction of the recording medium.

40. The recording medium of claim 38, wherein the recording medium is to be finalized when the TDMA is full and no more management information can be recorded in the TDMA.  
25

41. The recording medium of claim 40, wherein the latest management information recorded in at least one of the first and second areas of the DMA includes latest temporary defect list information and latest temporary disc definition structure information associated with the recording medium.

42. The recording medium of claim 38, wherein the recording medium is to be finalized in response to a user's request.

5           43. The recording medium of claim 42, wherein the latest management information recorded in at least one of the first and second areas of the DMA includes latest temporary defect list information and latest temporary disc definition structure information associated with the recording medium.

10           44. The recording medium of claim 28, wherein the recording medium is a writable-once Blu-ray disc (BD-WO).

            45. The recording medium of claim 28, wherein the latest management information includes a status flag indicating a type of the DMA fill-in stage.

15

            46. A write-once optical recording medium for recording management information thereon, the recording medium comprising:

                at least one recording layer including a temporary defect management area (TDMA) and a final defect management area (DMA), the DMA including a defect

20      list area for storing therein defect list information,

                wherein if no defect management is to be performed on the recording medium, a predetermined value is set in the defect list area of the DMA,

                management information produced while the recording medium is in use is recorded in the TDMA, and

25           the latest management information of the TDMA is transferred and recorded in the DMA when the recording medium is to be finalized.

            47. The recording medium of claim 46, wherein the DMA further includes a disc definition structure area for storing therein disc definition structure information,

and

wherein when the recoding medium is to be finalized, the latest management information of the TDMA is transferred to the disc definition structure area of the DMA and is latest disc definition structure information associated with the recording  
5 medium.

48. The recording medium of claim 46, wherein the recording medium is to be finalized when no more recording in a user data area of the recording medium is allowed.

10


49. The recording medium of claim 46, wherein the recording medium is to be finalized when the TDMA is full and no more management information can be recorded in the TDMA.

15 50. The recording medium of claim 46, wherein the recording medium is to be finalized in response to a user's request.

51. The recording medium of claim 46, wherein the recording medium is a writable-once Blu-ray disc (BD-WO).

20 52. The recording medium of claim 46, wherein the latest management information includes a status flag indicating a type of the finalization of the recording medium.

FIG. 1  
Background Art





2/11

FIG. 2






FIG. 3



4/11

FIG. 4



\* Recording mode

- 0000 0000b : Sequential Recording
- 0000 0001b : Random Recording



6/11

FIG. 6A




Single Layer BD- WO

FIG. 6B



8/11

FIG. 6C

Dual Layer BD-WO

9/11

FIG. 7

		DMA fill-in timing	contents	Location in DMA
Finalization	50a	No more record	Latest TDDS & TDFL	DDS & DFL
	50b	TDMA Full	Latest TDDS & TDFL	DDS & DFL
	50c	User selection	Latest TDDS & TDFL	DDS & DFL

FIG. 8

		DMA fill-in timing	contents	Location in DMA
	50d	Non D.M	Predetermined Value (ex, zero padding)	DFL
Finalization	50a	No more record	Latest TDDS	DDS
	50b	TDMA Full	Latest TDDS	DDS
	50c	User selection	Latest TDDS	DDS

- D.M : Defect Management
- DMA : Defect Management Area



10/11

FIG. 9A

	DMA fill-in timing	contents	Location in DMA
50e	No more record But Spare & TDMA left	Latest TDDS & TDFL	Part of DMA
50b	TDMA Full	Latest TDDS & TDFL	Remainder of DMA
50c	User selection	Latest TDDS & TDFL	Remainder of DMA

Finalization {

- D.M : Defect Management
- DMA : Defect Management Area

FIG. 9B

Clusters 1 ~ 2	DDS (before Finalization)
Clusters 3 ~ 4	DDS (at Finalization)
Clusters 5 ~ 8	DFL (before Finalization)
Clusters 9 ~ 12	1st position of DFL (at Finalization)
⋮	⋮
Clusters 29 ~ 32	6th position of DFL (at Finalization)

11/11

FIG. 10

(T)DDS status flag (1byte) in DMA/TDMA	
0000 0000	In DMA, after User select finalization
0000 1111	In DMA, after no more record
1111 0000	In DMA, after TDMA Full
1111 1111	In TDMA, before finalization

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/KR 03/02009-0

## CLASSIFICATION OF SUBJECT MATTER

IPC<sup>7</sup>: G11B 7/00, 11/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC<sup>7</sup>: G11B 7/00, 11/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

G11B 7/0045, 11/10, 11/12, 13/04, 20/10, 20/12

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5805536 A (Gage et al.) 8 September 1998 (08.09.98)	1,19,26-28,46
A	US 5247494 A (Ohno et al.) 21 September 1993 (21.09.93)	1,19,26-28,46
A	EP 0556046 A1 (Sony) 18 August 1993 (18.08.93)	1,19,26-28,46

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

\* Special categories of cited documents:

„A“ document defining the general state of the art which is not considered to be of particular relevance

„E“ earlier application or patent but published on or after the international filing date

„L“ document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

„O“ document referring to an oral disclosure, use, exhibition or other means

„P“ document published prior to the international filing date but later than the priority date claimed

„T“ later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

„X“ document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

„Y“ document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

„&“ document member of the same patent family

Date of the actual completion of the international search

23 January 2004 (23.01.2004)

Date of mailing of the international search report

12 February 2004 (12.02.2004)

Name and mailing address of the ISA/AT

Austrian Patent Office

Dresdner Straße 87, A-1200 Vienna

Facsimile No. 1/53424/535

Authorized officer

GRÖSSING G.

Telephone No. 1/53424/386

Form PCT/ISA/210 (second sheet) (July 1998)

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/KR 03/02009-0

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
EP	A	556046		KR B 275000	2000-12-15
				DE T 69318053T	1998-08-20
				DE D 69318053D	1998-05-28
				US A 5309419	1994-05-03
				EP A 0556046	1993-08-18
				JP A 5225570	1993-09-03
US	A	5247494	1993-09-21	JP A 60263353	1985-12-26
US	A	5805536	1998-09-08	none	